

TINTY

COLORDISPENSER 



TINTING INTELLIGENCE 5.0

Technical datasheet

TINTA



Technical data

Dosing flow:	simultaneous
Pumps:	3 oz. piston pumps
Pastes:	water and solvent based
Canister:	POM (acetalic resin)
Canister volume:	2,5 l / 5,0 l (optional)
Housing options:	16 / 24 / 32 canisters
Valves:	ceramic butterfly valves
Ultra-small dosing quantity:	1/768 fl. oz. (0,04 ml)
Dosierkopf:	CoolNOZ
Container handling:	MoveNOZ, the dosing head can be moved up-/downwards
Max. container height:	450 mm
Max. container diameter:	380 mm
Machine dimensions (w x d x h):	TINTA 16: 1080 x 805 x 1255 mm TINTA 24: 1235 x 805 x 1255 mm TINTA 32: 1220 x 925 x 1255 mm
Weight of the machine:	TINTA 16: 134 kg TINTA 24: 142 kg TINTA 32: 150 kg
Height of fill level:	1220 mm
Power supply:	100 - 240 Volt \pm 10 %
Frequency:	50/60 Hz
Options:	Punch Laser indicator PC option Extractable shelf for small cans Customized billboards Holders for keyboards, printers, scanners or spectros

 **Collomix**
colorTEC

Collomix GmbH
Daimlerstraße 9 · 85080 Gaimersheim/Germany · www.collomix.com